

Atlas Copco Reciprocating air compressors

KT Series 5-15HP





The Atlas Copco KT Series is designed for the industrial application that demands reliable, high performance continuous operation.

Standard Features

- Heavy-duty, cast-iron compressor
- Factory fill lubricant
- ODP electric motors, 3450 or 1750 rpm
- Single-phase 230 volt and three-phase 208/230/460 volt
- 60, 80 or 120 gallon air receivers on simplex models; up to 240 gallon on duplex models
- Splash lubricated
- Filter-silencers
- One-year warranty on complete unit

Optional Features

- 208/230/460/575 volt magnetic starters mounted and wired
- Factory installed air cooled aftercoolers
- Moisture separator and drain trap (with aftercooler)
- Electronic or pneumatic tank drains
- California code 462L OSHA approval available on request
- Massachusetts code
- Vibration isolators
- Duplex control panels
- Low oil shutdown
- Optional two-year warranty kit on two-stage models

Model	CFM @ 175 psi	HP	Tank Size	Weight	L x W x H
KT51ec 60V 230/1/60	15.2	5	60V	500	37 x 22 x 73
KT5 80V 230/1/60	17.2	5	80V	580	37 x 24 x 73
KT5 80V 230/3/60	17.2	5	80V	580	37 x 24 x 73
KT5ec 80V 230/1/60	16.3	5	80V	580	37 x 24 x 73
KT7.5 80V 230/1/60	22.6	7.5	80V	580	37 x 24 x 74
KT7.5 80V 230/3/60	22.6	7.5	80V	580	37 x 24 x 74
KT7.5ec 80V 230/1/60	22.4	7.5	80V	580	37 x 24 x 74
KT10 120V 230/3/60	35	10	120V	1000	40 x 30 x 75
KT15 120H 230/3/60	52.5	15	120H	995	78 x 28 x 55
KT15 120H 460/3/60	52.5	15	120H	995	78 x 28 x 55



Danger: Never use compressed air as breathing air without prior purification in accordance with local legislation and standards. Atlas Copco assumes no responsibility or liability related to the purchaser's/user's breathing air system.

The information contained herein is general in nature and is not intended for specific construction, installation or application purposes.



Atlas Copco Compressors Inc.
 94 North Elm Street, Floor 4
 Westfield, MA 01085-1689
 Tel. 413-536-0600 Fax. 413-536-0091
 www.atlascopco.us